


Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
3 LRAFP 02/G2 IM M
- **Nitta Japan code:**
GU-21A



Construction:	3 plies polyester, rigid, antistatic		
	TOP COVER	INNER LAYER	BOTTOM SIDE
Material:	PU	PU	Impregnated antistatic fabric
Thickness:	0,2	-	mm (approx.)
Colour:	Dark green	White	-
Hardness:	87 Shore A	-	-
Profile:	matt	-	-
Total thickness:	2,5		mm (approx.)
Weight:	2,6		kg/m ² (approx.)
Max. width:	3000		mm
Belt support:	Sliderbed (Rollers), Flat		
Rating at 1% elongation:	12		N/mm
Advised pretension:	5 - 8		N/mm
Maximum allowable tension:	18		N/mm
Temperature range:	-20	to +80	°C
Minimum pulley diameters:			
Flexing:	80		mm
Backflexing:	120		mm
Special approval:	FDA, 10/2011/EC + amendments		
Applications:	General purpose conveying Heavy duty applications Swanneck conveyors Accumulation belt for folder gluer machines		

Date of issue 21-10-2014-1